

Sample commands

```
testdatabase 'testsietske';
```

```
> mysql -u root

MariaDB [testsietske]> use testsietske;

MariaDB [testsietske]> show tables;

MariaDB [testsietske]> select * from City;

MariaDB [testsietske]> select * from City where Countrycode = "NLD";

MariaDB [testsietske]> select * from City where District = "Noord-Holland";

MariaDB [testsietske]> select * from City where Countrycode = "NLD" and population >
"100000";

MariaDB [testsietske]> show tables;

MariaDB [testsietske]> select * from Country where Continent = "Europe";

----
```

- You can use `db_name.tbl_name` as an alternative to the `tbl_name FROM db_name` syntax. In other words, these two statements are equivalent:

```
SHOW COLUMNS FROM City;
MariaDB [testsietske]> SHOW COLUMNS FROM mytable FROM mydb;
MariaDB [testsietske]> SHOW COLUMNS FROM mydb.mytable;
```

- show only first 10 results

```
MariaDB [testsietske]> select * from City limit 10;
```

- show result 10 to 30

```
MariaDB [testsietske]> select * from City limit 20 offset 10;
```

Revision #3

Created 2026-04-01 17:13:43 CEST by Philip

Updated 2026-04-13 19:24:56 CEST by Philip