

A810 S/N: _____		tape speed								date: _____	table of tape adjustments																								
TAPE: A <input type="checkbox"/> / B <input type="checkbox"/>		30		15		7 ½		3 ¾		remarks:	<table border="1"> <tr> <td></td> <td style="text-align: center;">30</td> </tr> <tr> <td>tape A</td> <td></td> </tr> <tr> <td>tape B</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">15</td> </tr> <tr> <td>tape A</td> <td style="text-align: center;">SM911</td> </tr> <tr> <td>tape B</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">7 ½</td> </tr> <tr> <td>tape A</td> <td></td> </tr> <tr> <td>tape B</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">3 ¾</td> </tr> <tr> <td>tape A</td> <td></td> </tr> <tr> <td>tape B</td> <td></td> </tr> </table>		30	tape A		tape B			15	tape A	SM911	tape B			7 ½	tape A		tape B			3 ¾	tape A		tape B	
	30																																		
tape A																																			
tape B																																			
	15																																		
tape A	SM911																																		
tape B																																			
	7 ½																																		
tape A																																			
tape B																																			
	3 ¾																																		
tape A																																			
tape B																																			
EQ: NAB <input type="checkbox"/> / CCIR <input type="checkbox"/>		ch. 1	ch. 2	ch. 1	ch. 2	ch. 1	ch. 2	ch. 1	ch. 2																										
REPRO	level																																		
	treble																																		
	bass																																		
	eq.																																		
RECORD	level																																		
	treble																																		
	bias																																		
	eq.																																		
SYNC ⁴⁾	level																																		
	treble																																		
	bass																																		
	eq.																																		

1) remember to put switch 8 on the Periphery Controller Card to **ON** first, and to return it to **OFF** when done entering data.

2) tape EQ is always **AES** (fixed) @ **30 IPS**, and always **NAB** (fixed) @ **3¾ IPS**

3) updated versions can be found at: <https://www.reeltoreel.nl/>

4) press 'sync' and read repro levels

20220505

Version 2.0

Philip van der Matten